



# **FEATURES**

- Special customized woofer unit, bassreflex design, full and elastic sound
- Quick setup for stacking and supporting
- Applications: multifunction halls, lecture halls, large classrooms, churches and touring

## 产品特征

- ●特制低音单元,直射倒相式箱体结构设计, 保证音质丰满且有弹性
- ●多种组合使用方式: 堆码、支撑, 安装快捷、安全

## 适用范围

- ●多功能厅、报告厅、教堂
- ●小型流动演出

# **DLAseries DLA815BAS**

Line Array System


**DLA815BAS** is an active subwoofer system, equipped with a three channels digital amplifier with DSP, drive itself 15" subwoofer, can also drive two DLA803, form a small system, can support and stack combination, meet a variety of small scenarios, system combination is convenient and fast. Unit configuration: 1x15" 75mm voice coil special designed woofer unit, bass-reflex design. The cabinet is made of multilayer composite plywood with wear-resistant polyurea paint.

DLA815BAS是一款功能强大的有源超低音箱系统,直射倒相式箱体结构设计,配置一台三通道带DSP处理功能的功放,驱动自身15"超低音外,还可驱动两只DLA803,组成小型系统,可支撑、堆码组合,满足多种小型场景使用,系统组合方便快捷,单元配置:1只15"75芯特制低音单元,箱体采用多层复合夹板,耐磨聚脲喷涂。



## CONFIGURATION





MODEL
FREQUENCY RESPONSE(-3dB)
DRIVERS
RATED POWER
SENSITIVITY
MAXIMUM SPL
IMPEDANCE
INPUT CONNECTORS
PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

DLA815BAS

40Hz-300Hz and 50Hz-20kHz  $1\times15"(385mm)/3"voice coil LF 400W/8<math display="inline">\Omega$ +400W/8 $\Omega$ +800W/8 $\Omega$ 

125dB continuous,131dB peak

INPUT TYPE: Balanced Differential line

 $600 mm \times 520 mm \times 680 mm$ 

34 kg/pc 37 kg/pc

