



FT series FT15 II

Two-way Loudspeaker System

The FT15 II is a 15" two-way full range speaker. Unit configuration: 1x15" high efficiency mid-bass unit, 1x1" exit throat 34mm titanium diaphragm HF driver with 80°×50° rotatable horn. The cabinet is made of MDF with water-based environmental protection paint.

FT15 II 是一款15"两分音全音域音箱。单元配置：1只15"高效率低音单元，1只1"喉口34芯钛膜高音驱动器配置80°×50°可旋转号角。箱体采用高密度复合板，水性环保喷涂制作。

FEATURES

- High quality MDF housing
- Multi-hanging points and support, easy and quick operation
- Applications: full range reinforcement, speech and conference halls, multifunction halls, classrooms, small outdoor reinforcement



产品特征

- 高强度复合板箱体
- 多吊挂点与支撑配合，操作简易快捷

适用范围

- 用于全音域扩声、语言会议系统
- 多功能厅、学校教室
- 小型室外扩声

CONFIGURATION



MODEL

FREQUENCY RESPONSE(-3dB)

FREQUENCY RESPONSE(-10dB)

DRIVERS

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

DISPERSION(-6dB)

CROSSOVER FREQUENCIES

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

FT15 II

40Hz-20kHz

35Hz-20kHz

1×15"(385mm)/2.5" voice coil LF

1×1"(25mm)/ 1.4"voice coil HF

300W RMS,1200W peak

97dB 1watt/1 metre

122 dB continuous,128 dB peak

8 ohms nominal

80°×50°

2kHz passive

2×Speakon NL4

565mm×545mm×795mm

27 kg/pc

30 kg/pc

