



pro audio



PLA series PLA212B

Line Array System

FEATURES

- Pass IP66 testing
- Polymer composite material mold forming box, five layers of waterproof, dustproof composite grille, strong weather resistance
- Can be matched with PLA312, PLA410 and PLA612
- Applications: outdoor fixed installation

系统特征

- 通过IP66测试
- 工程塑胶模具成型箱体，五层防水、防尘复合面网、耐候性极强
- 可与PLA312、PLA410、PLA612配合使用



适用范围

- 户外固定安装

PLA212B is a dual 12", all-weather subwoofer, designed with priority given to waterproof, dustproof, windproof, anti-uv aging, and five-layer grille design of different materials. The product meets the IP66 standard, all hanging parts and connecting parts are made of stainless steel, three-point hanging system, ensure safety. Can be matched with PLA312, PLA410, PLA612 to improve the low frequency performance of the system. Unit configuration: 2x12" customized mid-bass unit. The cabinet is made of polymer composite material through a special process.

PLA212B是一款双12"全天候超低音箱，产品设计优先考虑防水、防尘、防风、抗紫外线老化、五层不同材质面网设计。产品满足IP66标准，所有吊挂件、连接件采用不锈钢或铝质喷涂，三点吊挂系统，保证安全。与PLA312、PLA410、PLA612配合使用，以提升系统低音表现，单元配置：2只12"特制低音单元，箱体采用高分子复合材料经过特殊工艺成型。

CONFIGURATION



MODEL
FREQUENCY RESPONSE(-10dB)
DRIVERS
RATED POWER
SENSITIVITY
MAXIMUM SPL
IMPEDANCE
INPUT CONNECTORS
PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

PLA212B
50Hz-300Hz
2×12"(300mm)/3"voice coil LF
600W RMS, 2400W peak
98dB 1watt/1meter
126dB continuous,132dB peak
8 ohms nominal
2×Speakon NL4
700mm×524mm×931mm
33 kg/pc
40 kg/pc